



**General
Mills**

**Making Food
People Love**

315 Status Details (Ocean)

X12/V4010/315 : 315 Status Details (Ocean)

Company:

General Mills

Modified:

1/11/2018

Notes:

Table of Contents

315 Status Details (Ocean)..... 1

ISA Interchange Control Header..... 2

GS Functional Group Header..... 4

ST Transaction Set Header..... 6

B4 Beginning Segment for Inquiry or Reply..... 7

N9 Reference Identification..... 8

Q2 Status Details (Ocean)..... 9

R4 Loop Port or Terminal..... 10

R4 Port or Terminal..... 11

DTM Date/Time Reference..... 12

SE Transaction Set Trailer..... 13

GE Functional Group Trailer..... 14

IEA Interchange Control Trailer..... 15

315 Status Details (Ocean)

Functional Group=QO

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Status Details (Ocean) Transaction Set (315) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide all the information necessary to report status or event details for selected shipments or containers. It is intended to accommodate the details for one status or event associated with many shipments or containers, as well as more than one status or event for one shipment or container.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	B4	Beginning Segment for Inquiry or Reply	M	1			Must use
030	N9	Reference Identification	O	30			Used
040	Q2	Status Details (Ocean)	O	1			Used

LOOP ID - R4

20

060	R4	Port or Terminal	M	1			Must use
070	DTM	Date/Time Reference	O	15			Used
090	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Authorization Information All valid standard codes are used. (Total Codes: 7)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Security Information All valid standard codes are used. (Total Codes: 2)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used. (Total Codes: 38)						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified CodeList Summary (Total Codes: 38, Included: 1) <u>Code</u> <u>Name</u> 08 UCC EDI Communications ID (Comm ID)						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them General Mills Note: <i>General Mills ID = 9251190000</i>						
ISA09	I08	Interchange Date	M	DT	6/6	Must use
Description: Date of the interchange						
ISA10	I09	Interchange Time	M	TM	4/4	Must use
Description: Time of the interchange						
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used. (Total Codes: 1)						
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
Description: Code specifying the version number of the interchange control segments CodeList Summary (Total Codes: 14, Included: 1) <u>Code</u> <u>Name</u> 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997						
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
Description: Code sent by the sender to request an interchange acknowledgment (TA1) All valid standard codes are used. (Total Codes: 2)						
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information CodeList Summary (Total Codes: 3, Included: 1) <u>Code</u> <u>Name</u> P Production Data						
ISA16	I15	Component Element Separator	M		1/1	Must use
Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator						

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use

Description: Code identifying a group of application related transaction sets

CodeList Summary (Total Codes: 240, Included: 1)

Code Name

QO Ocean Shipment Status Information (313, 315)

GS02	142	Application Sender's Code	M	AN	2/15	Must use
------	-----	----------------------------------	---	----	------	----------

Description: Code identifying party sending transmission; codes agreed to by trading partners

GS03	124	Application Receiver's Code	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

Description: Code identifying party receiving transmission; codes agreed to by trading partners

General Mills Note:

General Mills ID = 6125404455

GS04	373	Date	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

GS05	337	Time	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	Group Control Number	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

Description: Assigned number originated and maintained by the sender

GS07	455	Responsible Agency Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480

CodeList Summary (Total Codes: 2, Included: 1)

Code Name

X Accredited Standards Committee X12

GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
------	-----	---	---	----	------	----------

Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed

CodeList Summary (Total Codes: 39, Included: 1)

Code Name

004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use				
Description: Code uniquely identifying a Transaction Set										
CodeList Summary (Total Codes: 298, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>315</td><td>Status Details (Ocean)</td></tr></table>							<u>Code</u>	<u>Name</u>	315	Status Details (Ocean)
<u>Code</u>	<u>Name</u>									
315	Status Details (Ocean)									
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use				
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set										

Semantics:

- 1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

B4 Beginning Segment for Inquiry or Reply

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
B403	157	Shipment Status Code	O	ID	1/2	Used

Description: Code indicating the status of a shipment

CodeList Summary (Total Codes: 175, Included: 1)

Code **Name**

VD Vessel Departure

Description: *Vessel scheduled to depart or has departed*

B404	373	Date	O	DT	8/8	Used
------	-----	------	---	----	-----	------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. P0708 - If either B407 or B408 is present, then the other is required.
2. P1112 - If either B411 or B412 is present, then the other is required.

Semantics:

1. B404 is the date of last reported status of cargo.

N9 Reference Identification

Pos: 030	Max: 30
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

General Mills Note:

SCA= Forwarder's SCAC code

VN= Prelim shipment number

CodeList Summary (Total Codes: 1503, Included: 5)

Code Name

FN Forwarder's/Agent's Reference Number

OC Ocean Container Number

SN Seal Number

VN Vendor Order Number

SCA Standard Carrier Alpha Code (SCAC)

N902	127	Reference Identification	X	AN	1/30	Used
------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

Q2 Status Details (Ocean)

Pos: 040	Max: 1
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Used

Purpose: To transmit identifying information relative to identification of vessel, transportation dates, lading quantity, weight, and cube

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
Q201	597	Vessel Code	O	ID	1/8	Used
		Description: Code identifying vessel				
Q204	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
		General Mills Note: <i>Date of vessel departure (sail date)</i>				
Q205	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
		General Mills Note: <i>ETA</i>				
Q209	55	Flight/Voyage Number	O	AN	2/10	Used
		Description: Identifying designator for the particular flight or voyage on which the cargo travels				
Q213	182	Vessel Name	O	AN	2/28	Used
		Description: Name of ship as documented in "Lloyd's Register of Ships"				

Syntax Rules:

1. P070816 - If either Q207, Q208 or Q216 are present, then the others are required.
2. C1011 - If Q210 is present, then Q211 is required.
3. P1415 - If either Q214 or Q215 is present, then the other is required.

Semantics:

1. Q202 is the code identifying the country in which the ship (vessel) is registered.
2. Q203 is the required pier date.
3. Q204 is the date of departure of the vessel.
4. Q205 is the date the shipment was unloaded from the vessel.

Loop Port or Terminal

Pos: 060	Repeat: 20
Mandatory	
Loop: R4	Elements: N/A

User Option (Usage): Must use
Purpose: Contractual or operational port or point relevant to the movement of the cargo

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
060	R4	Port or Terminal	M	1		Must use
070	DTM	Date/Time Reference	O	15		Used

R4 Port or Terminal

Pos: 060	Max: 1
Heading - Mandatory	
Loop: R4	Elements: 4

User Option (Usage): Must use

Purpose: Contractual or operational port or point relevant to the movement of the cargo

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
R401	115	Port or Terminal Function Code	M	ID	1/1	Must use
Description: Code defining function performed at the port or terminal with respect to a shipment						
CodeList Summary (Total Codes: 30, Included: 3)						
<u>Code</u> <u>Name</u>						
D Port of Discharge (Operational)						
Description: Port at which cargo is unloaded from vessel						
L Port of Loading (Operational)						
Description: Port at which cargo is loaded on vessel						
N Final Destination (Operational)						
Description: Consignee's facility at which shipment ends its movement at cargo's expense						
R402	309	Location Qualifier	X	ID	1/2	Used
Description: Code identifying type of location						
CodeList Summary (Total Codes: 172, Included: 2)						
<u>Code</u> <u>Name</u>						
D Census Schedule D						
K Census Schedule K						
R403	310	Location Identifier	X	AN	1/30	Used
Description: Code which identifies a specific location						
R404	114	Port Name	O	AN	2/24	Used
Description: Free-form name for the place at which an offshore carrier originates or terminates (by transshipment or otherwise) its actual ocean carriage of property						

Syntax Rules:

1. P0203 - If either R402 or R403 is present, then the other is required.

Comments:

1. R4 is required for each port to be identified.

DTM

Date/Time Reference

Pos: 070

Max: 15

Heading - Optional

Loop: R4

Elements: 2

User Option (Usage): Used
Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use				
Description: Code specifying type of date or time, or both date and time										
General Mills Note: 371 = Subsequent leg arrival at customer										
CodeList Summary (Total Codes: 1112, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>371</td><td>Estimated Arrival Date</td></tr></table>							<u>Code</u>	<u>Name</u>	371	Estimated Arrival Date
<u>Code</u>	<u>Name</u>									
371	Estimated Arrival Date									
DTM02	373	Date	X	DT	8/8	Used				
Description: Date expressed as CCYYMMDD										

- Syntax Rules:
- 1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
 - 2. C0403 - If DTM04 is present, then DTM03 is required.
 - 3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

SE Transaction Set Trailer

Pos: 090	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

- 1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						