



**General
Mills**

**Making Food
People Love**

846 Inventory Inquiry/Advice

UCS/V4010/846: 846 Inventory Inquiry/Advice

Company:

General Mills

Modified:

1/11/2018

Notes:

Daily Inventory Snapshot

Table of Contents

846 Inventory Inquiry/Advice 1

ISA Interchange Control Header 2

GS Functional Group Header 4

ST Transaction Set Header 6

BIA Beginning Segment for Inventory Inquiry/Advice 7

N1 Loop Name 8

N1 Name 9

LIN Loop Item Identification 10

LIN Item Identification 11

DTM Date/Time Reference 13

REF Reference Identification 14

QTY Loop Quantity 15

QTY Quantity 16

CTT Transaction Totals 17

SE Transaction Set Trailer 18

GE Functional Group Trailer 19

IEA Interchange Control Trailer 20

846 Inventory Inquiry/Advice

Functional Group=**IB**

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Inventory Inquiry/Advice Transaction Set (846) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used in the following ways: (1) for a seller of goods and services to provide inventory information to a prospective purchaser, with no obligation to the purchaser to acquire these goods or services; (2) for a representative of a seller of goods and services to supply inventory information to that seller; (3) for one location to supply another location with inventory information; and (4) for an inquiry as to the availability of inventory with no obligation on the seller of goods and services to reserve that inventory.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BIA	Beginning Segment for Inventory Inquiry/Advice	M	1			Must use

<u>LOOP ID - N1</u>					<u>5</u>		
080	N1	Name	O	1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - LIN</u>					<u>10000</u>		
010	LIN	Item Identification	M	1			Must use
100	DTM	Date/Time Reference	O	10			Used
140	REF	Reference Identification	O	>1			Used
<u>LOOP ID - QTY</u>					<u>99</u>		
320	QTY	Quantity	O	1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of number of LIN segments. If used, hash total (CTT02) is the sum of the values of the quantities (QTY02) of each QTY segment.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Authorization Information All valid standard codes are used. (Total Codes: 7)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Security Information All valid standard codes are used. (Total Codes: 2)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used. (Total Codes: 38)						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified CodeList Summary (Total Codes: 38, Included: 1) <u>Code</u> <u>Name</u> 08 UCC EDI Communications ID (Comm ID)						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them General Mills Note: <i>General Mills Test ID = 925119TEST</i> <i>General Mills Production ID = 9251190000</i>						
ISA09	I08	Interchange Date	M	DT	6/6	Must use
Description: Date of the interchange						
ISA10	I09	Interchange Time	M	TM	4/4	Must use
Description: Time of the interchange						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used. (Total Codes: 1)						
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
Description: Code specifying the version number of the interchange control segments CodeList Summary (Total Codes: 13, Included: 1) <u>Code</u> <u>Name</u> 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997						
ISA13	I12	Interchange Control Number	M	NO	9/9	Must use
Description: A control number assigned by the interchange sender						
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
Description: Code sent by the sender to request an interchange acknowledgment (TA1) All valid standard codes are used. (Total Codes: 2)						
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information CodeList Summary (Total Codes: 3, Included: 1) <u>Code</u> <u>Name</u> P Production Data						
ISA16	I15	Component Element Separator	M		1/1	Must use
Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator						

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
Description: Code identifying a group of application related transaction sets						
CodeList Summary (Total Codes: 225, Included: 1)						
<u>Code</u> <u>Name</u>						
IB Inventory Inquiry/Advice (846)						
GS02	142	Application Sender's Code	M	AN	2/15	Must use
Description: Code identifying party sending transmission; codes agreed to by trading partners						
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
Description: Code identifying party receiving transmission; codes agreed to by trading partners						
General Mills Note:						
<i>General Mills Test & Production ID = 6125404455</i>						
GS04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
GS05	337	Time	M	TM	4/8	Must use
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
GS06	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
Description: Code used in conjunction with Data Element 480 to identify the issuer of the standard						
CodeList Summary (Total Codes: 2, Included: 1)						
<u>Code</u> <u>Name</u>						
T Transportation Data Coordinating Committee (TDCC)						
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed						
CodeList Summary (Total Codes: 33, Included: 1)						
<u>Code</u> <u>Name</u>						
004010UCS Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997						

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use				
Description: Code uniquely identifying a Transaction Set										
CodeList Summary (Total Codes: 298, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>846</td><td>Inventory Inquiry/Advice</td></tr></table>							<u>Code</u>	<u>Name</u>	846	Inventory Inquiry/Advice
<u>Code</u>	<u>Name</u>									
846	Inventory Inquiry/Advice									
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use				
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set										

Semantics:

- 1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BIA Beginning Segment for Inventory Inquiry/Advice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To indicate the beginning of an Inventory Inquiry/Advice Transaction Set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BIA01	353	Transaction Set Purpose Code	M	ID	2/2	Must use
Description: Code identifying purpose of transaction set						
CodeList Summary (Total Codes: 65, Included: 1)						
<u>Code</u> <u>Name</u>						
08 Status						
BIA02	755	Report Type Code	M	ID	2/2	Must use
Description: Code indicating the title or contents of a document, report or supporting item						
CodeList Summary (Total Codes: 522, Included: 1)						
<u>Code</u> <u>Name</u>						
LC Location Inventory Report						
BIA03	127	Reference Identification	M	AN	1/30	Must use
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						
BIA04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
General Mills Note: <i>Effective date of the transmission.</i>						

Semantics:

1. BIA03 identifies the number of the inquiry/advice that is transferred.
2. BIA04 identifies the date of the inquiry/advice that is transferred.
3. BIA05 identifies the time of the inquiry/advice that is transferred.

Loop Name

Pos: 080	Repeat: 5
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used
Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
080	N1	Name	O	1		Used

N1 Name

Pos: 080	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use
Description: Code identifying an organizational entity, a physical location, property or an individual						
CodeList Summary (Total Codes: 1312, Included: 1)						
<u>Code</u> <u>Name</u>						
WH Warehouse						
N102	93	Name	C	AN	1/60	Used
Description: Free-form name						
N103	66	Identification Code Qualifier	C	ID	1/2	Must use
Description: Code designating the system/method of code structure used for Identification Code (67)						
CodeList Summary (Total Codes: 215, Included: 1)						
<u>Code</u> <u>Name</u>						
9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix						
N104	67	Identification Code	C	AN	2/80	Must use
Description: Code identifying a party or other code						

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

Loop Item Identification

Pos: 010	Repeat: 10000
Mandatory	
Loop: LIN	Elements: N/A

User Option (Usage): Must use
Purpose: To specify basic item identification data

Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
010	LIN	Item Identification	M	1		Must use
100	DTM	Date/Time Reference	O	10		Used
140	REF	Reference Identification	O	>1		Used
320		Loop QTY	O		99	Used

Semantics:

- 1. LIN01 is the line item identification

Comments:

- 1. See the Data Dictionary for a complete list of IDs.
- 2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

LIN Item Identification

Pos: 010	Max: 1
Detail - Mandatory	
Loop: LIN	Elements: 6

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN02	235	Product/Service ID Qualifier	M	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 477, Included: 1)						
Code Name						
VN Vendor's (Seller's) Item Number						
LIN03	234	Product/Service ID	M	AN	1/48	Must use
Description: Identifying number for a product or service						
General Mills Note: The 10-digit General Mills material number.						
LIN04	235	Product/Service ID Qualifier	C	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 477, Included: 1)						
Code Name						
GC Grade Code						
LIN05	234	Product/Service ID	C	AN	1/48	Must use
Description: Identifying number for a product or service						
General Mills Note:						
<i>Statuses:</i>						
<i>BL = Blocked</i>						
<i>QI = Quality Inspection</i>						
<i>UR = Unrestricted (Available)</i>						
<i>QR = Quality Restricted (Project Green Light)</i>						
LIN06	235	Product/Service ID Qualifier	C	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 477, Included: 1)						
Code Name						
DV Location Code						
LIN07	234	Product/Service ID	C	AN	1/48	Used
Description: Identifying number for a product or service						
General Mills Note: Use this for reporting inventory in an alternative storage location (such as PR). If not filled in, this defaults to WA storage location for your site.						

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.

7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

Comments:

1. See the Data Dictionary for a complete list of IDs.
2. LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

General Mills Note:

Notes regarding status (LIN05):

If a material/batch is restricted and also in blocked stock; blocked "wins" and it should be shown as blocked in this transaction.

*In our SAP application there are 3 main Inventory statuses: UR (Available), BL (Blocked) and QI (Incubation). The Green Light status is actually the status of the **batch** not technically the **inventory**. The only time on the 846 we want to see the batch status of QR (restricted) is when the batch is in QR status and the inventory status is available. Otherwise, send the status of the inventory (BL or QI).*

Quality Inspection (QI) applies to other types of testing (such as incubation holds). It also trumps QR or UR status as above.

DTM Date/Time Reference

Pos: 100	Max: 10
Detail - Optional	
Loop: LIN	Elements: 2

User Option (Usage): Used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Used

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 2)

Code Name

036 Expiration

Description: *Date coverage expires*

405 Production

Description: *Used to identify dates and times that operations or processes were performed*

DTM02	373	Date	C	DT	8/8	Used
-------	-----	------	---	----	-----	------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

General Mills Note:

This segment must be sent for all SAP batch managed materials. Otherwise it is an optional segment.

REF Reference Identification

Pos: 140	Max: >1
Detail - Optional	
Loop: LIN	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 1)

Code Name

LT Lot Number

REF02	127	Reference Identification	C	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

General Mills Note:

The REF02 should contain either the GMI Lot Code (aka Date Code) if the Material was produced for General Mills or the Vendor's Lot Code.

If the Material was produced for General Mills, the format needs to be DDMMYYXX (where XX is the two-digit Producing Location identifier).

This format may appear on the case or shipping container with a four-digit year, but only include the last digit in this electronic format.

If the material is from a vendor, the vendor's lot code format should be used. This will vary by vendor.

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Loop Quantity

Pos: 320	Repeat: 99
Optional	
Loop: QTY	Elements: N/A

User Option (Usage): Used
Purpose: To specify quantity information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
320	QTY	Quantity	O	1		Used

Semantics:

- 1. QTY04 is used when the quantity is non-numeric.

QTY Quantity

Pos: 320	Max: 1
Detail - Optional	
Loop: QTY	Elements: 3

User Option (Usage): Used

Purpose: To specify quantity information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
QTY01	673	Quantity Qualifier	M	ID	2/2	Must use

Description: Code specifying the type of quantity

CodeList Summary (Total Codes: 832, Included: 1)

Code Name

17 Quantity on Hand

QTY02	380	Quantity	C	R3	1/15	Must use
-------	-----	----------	---	----	------	----------

Description: Numeric value of quantity

General Mills Note: Do not use decimals.

Use a minus sign in front of negative values.

QTY03	355	Unit or Basis for Measurement Code	O	ID	2/2	Must use
-------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

General Mills Note: These codes represent the most commonly used Base Unit Of Measurement Codes within General Mills.

If your facility produces product for General Mills, a more comprehensive list may be needed for your operations. Please discuss your needs with a General Mills EDI support person. General Mills EDI support can provide a comprehensive list of all Base UOM codes or a list of codes specific to your location.

CodeList Summary (Total Codes: 794, Included: 7)

Code Name

BG Bag
CA Case
CW Hundred Pounds (CWT)
EA Each
FT Foot
LB Pound
PL Pallet/Unit Load

Syntax Rules:

1. R0204 - At least one of QTY02 or QTY04 is required.
2. E0204 - Only one of QTY02 or QTY04 may be present.

Semantics:

1. QTY04 is used when the quantity is non-numeric.

CTT Transaction Totals

Pos: 010

Max: 1

Summary - Optional

Loop: N/A

Elements: 1

User Option (Usage): Used
Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use
Description: Total number of line items in the transaction set						
General Mills Note: Contains the number of LIN segments present in the transaction set.						

Syntax Rules:

- 1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
- 2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

- 1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

- 1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						