



**General  
Mills**

**Making Food  
People Love**

## **855 Purchase Order Acknowledgment**

**UCS/V4010/855: 855 Purchase Order Acknowledgment**

**Company:**

**Modified:**

**Notes:**

**General Mills**

**1/11/2018**

**General Mills use:**

**Copy of Vendor Purchase  
Order going to receiving  
location**

# Table of Contents

<b>855</b>	<b>Purchase Order Acknowledgment</b>	<b>1</b>
ISA	Interchange Control Header	3
GS	Functional Group Header	5
ST	Transaction Set Header	7
BAK	Beginning Segment for Purchase Order Acknowledgment	8
DTM	Date/Time Reference	9
N1	Loop Name	10
N1	Name	11
N3	Address Information	12
N4	Geographic Location	13
PO1	Loop Baseline Item Data	14
PO1	Baseline Item Data	15
PID	Loop Product/Item Description	17
PID	Product/Item Description	18
N9	Loop Reference Identification	19
N9	Reference Identification	20
MSG	Message Text	21
CTT	Loop Transaction Totals	22
CTT	Transaction Totals	23
SE	Transaction Set Trailer	24
GE	Functional Group Trailer	25
IEA	Interchange Control Trailer	26

# 855 Purchase Order Acknowledgment

Functional Group=PR

**Purpose:** This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Acknowledgment Transaction Set (855) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to a seller's acknowledgment of a buyer's purchase order. This transaction set can also be used as notification of a vendor generated order. This usage advises a buyer that a vendor has or will ship merchandise as prearranged in their partnership.

## Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

## Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BAK	Beginning Segment for Purchase Order Acknowledgment	M	1			Must use
150	DTM	Date/Time Reference	O	10			Used

### LOOP ID - N1 200

300	N1	Name	O	1			Used
320	N3	Address Information	O	2			Used
330	N4	Geographic Location	O	1			Used

## Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - PO1</u>					<u>100000</u>	<u>N2/010L</u>	
010	PO1	Baseline Item Data	O	1		N2/010	Used
<u>LOOP ID - PID</u>					<u>1000</u>		
050	PID	Product/Item Description	O	1			Used
<u>LOOP ID - N9</u>					<u>1000</u>		
350	N9	Reference Identification	O	1			Used
360	MSG	Message Text	O	1000			Used

## Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - CTT</u>					<u>1</u>	<u>N3/010L</u>	
010	CTT	Transaction Totals	O	1		N3/010	Used
030	SE	Transaction Set Trailer	M	1			Must use

## Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

## Notes:

2/010L PO102 is required.

2/010 PO102 is required.

- 3/010L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/010 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

# ISA Interchange Control Header

<b>Pos:</b>	<b>Max: 1</b>
<b>Not Defined - Mandatory</b>	
<b>Loop: N/A</b>	<b>Elements: 16</b>

**User Option (Usage):** Must use

**Purpose:** To start and identify an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	<b>Authorization Information Qualifier</b>	M	ID	2/2	Must use
<b>Description:</b> Code to identify the type of information in the Authorization Information						
<b>CodeList Summary</b> (Total Codes: 7, Included: 1)						
<b>Code Name</b>						
00 No Authorization Information Present (No Meaningful Information in I02)						
ISA02	I02	<b>Authorization Information</b>	M	AN	10/10	Must use
<b>Description:</b> Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	<b>Security Information Qualifier</b>	M	ID	2/2	Must use
<b>Description:</b> Code to identify the type of information in the Security Information						
<b>CodeList Summary</b> (Total Codes: 2, Included: 1)						
<b>Code Name</b>						
00 No Security Information Present (No Meaningful Information in I04)						
ISA04	I04	<b>Security Information</b>	M	AN	10/10	Must use
<b>Description:</b> This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	<b>Interchange ID Qualifier</b>	M	ID	2/2	Must use
<b>Description:</b> Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified						
<b>CodeList Summary</b> (Total Codes: 38, Included: 1)						
<b>Code Name</b>						
08 UCC EDI Communications ID (Comm ID)						
ISA06	I06	<b>Interchange Sender ID</b>	M	AN	15/15	Must use
<b>Description:</b> Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
<b>General Mills Note:</b>						
<i>General Mills Test ID = 925119TEST</i>						
<i>General Mills Production ID = 9251190000</i>						
ISA07	I05	<b>Interchange ID Qualifier</b>	M	ID	2/2	Must use
<b>Description:</b> Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified						
<b>All valid standard codes are used. (Total Codes: 38)</b>						
ISA08	I07	<b>Interchange Receiver ID</b>	M	AN	15/15	Must use
<b>Description:</b> Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them						
ISA09	I08	<b>Interchange Date</b>	M	DT	6/6	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		<b>Description:</b> Date of the interchange				
ISA10	I09	<b>Interchange Time</b>	M	TM	4/4	Must use
		<b>Description:</b> Time of the interchange				
ISA11	I10	<b>Interchange Control Standards Identifier</b>	M	ID	1/1	Must use
		<b>Description:</b> Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer				
		<b>All valid standard codes are used. (Total Codes: 1)</b>				
ISA12	I11	<b>Interchange Control Version Number</b>	M	ID	5/5	Must use
		<b>Description:</b> Code specifying the version number of the interchange control segments				
		<b>CodeList Summary</b> (Total Codes: 13, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		00401	Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997			
ISA13	I12	<b>Interchange Control Number</b>	M	N0	9/9	Must use
		<b>Description:</b> A control number assigned by the interchange sender				
ISA14	I13	<b>Acknowledgment Requested</b>	M	ID	1/1	Must use
		<b>Description:</b> Code sent by the sender to request an interchange acknowledgment (TA1)				
		<b>All valid standard codes are used. (Total Codes: 2)</b>				
ISA15	I14	<b>Usage Indicator</b>	M	ID	1/1	Must use
		<b>Description:</b> Code to indicate whether data enclosed by this interchange envelope is test, production or information				
		<b>CodeList Summary</b> (Total Codes: 3, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		P	Production Data			
ISA16	I15	<b>Component Element Separator</b>	M		1/1	Must use
		<b>Description:</b> Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator				

# GS Functional Group Header

<b>Pos:</b>	<b>Max: 1</b>
<b>Not Defined - Mandatory</b>	
<b>Loop: N/A</b>	<b>Elements: 8</b>

**User Option (Usage):** Must use

**Purpose:** To indicate the beginning of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	<b>Functional Identifier Code</b>	M	ID	2/2	Must use
<b>Description:</b> Code identifying a group of application related transaction sets						
<b>CodeList Summary</b> (Total Codes: 225, Included: 1)						
<u>Code</u> <u>Name</u>						
PR   Purchase Order Acknowledgement (855)						
GS02	142	<b>Application Sender's Code</b>	M	AN	2/15	Must use
<b>Description:</b> Code identifying party sending transmission; codes agreed to by trading partners						
<b>General Mills Note:</b>						
General Mills Test & Production ID = 6125404455						
GS03	124	<b>Application Receiver's Code</b>	M	AN	2/15	Must use
<b>Description:</b> Code identifying party receiving transmission; codes agreed to by trading partners						
GS04	373	<b>Date</b>	M	DT	8/8	Must use
<b>Description:</b> Date expressed as CCYYMMDD						
GS05	337	<b>Time</b>	M	TM	4/8	Must use
<b>Description:</b> Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
GS06	28	<b>Group Control Number</b>	M	N0	1/9	Must use
<b>Description:</b> Assigned number originated and maintained by the sender						
GS07	455	<b>Responsible Agency Code</b>	M	ID	1/2	Must use
<b>Description:</b> Code used in conjunction with Data Element 480 to identify the issuer of the standard						
<b>CodeList Summary</b> (Total Codes: 2, Included: 1)						
<u>Code</u> <u>Name</u>						
T   Transportation Data Coordinating Committee (TDCC)						
GS08	480	<b>Version / Release / Industry Identifier Code</b>	M	AN	1/12	Must use
<b>Description:</b> Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed						
<b>CodeList Summary</b> (Total Codes: 33, Included: 1)						
<u>Code</u> <u>Name</u>						
004010UCS						

## Semantics:

- GS04 is the group date.

2. GS05 is the group time.
3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

**Comments:**

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.



# ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the start of a transaction set and to assign a control number

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

**Description:** Code uniquely identifying a Transaction Set

**CodeList Summary** (Total Codes: 298, Included: 1)

<u>Code</u>	<u>Name</u>
-------------	-------------

855	Purchase Order Acknowledgment
-----	-------------------------------

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

**Description:** Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

## Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

# BAK Beginning Segment for Purchase Order Acknowledgment

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

**User Option (Usage):** Must use

**Purpose:** To indicate the beginning of the Purchase Order Acknowledgment Transaction Set and transmit identifying numbers and dates

## Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
BAK01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

**Description:** Code identifying purpose of transaction set

**CodeList Summary** (Total Codes: 65, Included: 3)

**Code Name**

00 Original

**General Mills Note:**

*Notification of Product being shipped.*

01 Cancellation

**Description:** Cancellation of previously transmitted purchase order. On cancelled order, no line items (P01 segments) will be present.

**General Mills Note:**

*When sending cancellations, General Mills will send the header information for the PO, but no line items will be sent.*

05 Replace

**General Mills Note:**

*General Mills views this as a true replace transaction. 855s with '05' codes should overlay current version of the order in your system.*

BAK02	587	Acknowledgment Type	M	ID	2/2	Must use
-------	-----	---------------------	---	----	-----	----------

**Description:** Code specifying the type of acknowledgment

**General Mills Note:** Code AD will be sent on original orders. Code AC will be sent on all replace/cancel transactions.

**CodeList Summary** (Total Codes: 15, Included: 2)

**Code Name**

AC Acknowledge - With Detail and Change

AD Acknowledge - With Detail, No Change

BAK03	324	Purchase Order Number	M	AN	1/22	Must use
-------	-----	-----------------------	---	----	------	----------

**Description:** Identifying number for Purchase Order assigned by the orderer/purchaser

**General Mills Note:** General Mills Purchase Order Number

BAK04	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

**Description:** Date expressed as CCYYMMDD

**General Mills Note:** Purchase Order Create Date within General Mill's application

## Semantics:

1. BAK04 is the date assigned by the purchaser to purchase order.
2. BAK08 is the seller's order number.
3. BAK09 is the date assigned by the sender to the acknowledgment.

# DTM Date/Time Reference

Pos: 150	Max: 10
Heading - Optional	
Loop: N/A	Elements: 3

**User Option (Usage):** Used

**Purpose:** To specify pertinent dates and times

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

**Description:** Code specifying type of date or time, or both date and time

**CodeList Summary** (Total Codes: 1112, Included: 2)

### Code Name

002 Delivery Requested

#### **General Mills Note:**

*Date General Mills is expecting product delivered at ship-to location*

009 Process

#### **General Mills Note:**

*Date Purchase Order was transmitted.*

DTM02	373	Date	C	DT	8/8	Used
-------	-----	------	---	----	-----	------

**Description:** Date expressed as CCYYMMDD

DTM03	337	Time	C	TM	4/8	Used
-------	-----	------	---	----	-----	------

**Description:** Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

## Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

# Loop Name

Pos: 300	Repeat: 200
Optional	
Loop: N1	Elements: N/A

**User Option (Usage):** Used  
**Purpose:** To identify a party by type of organization, name, and code

**Loop Summary:**

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
300	N1	Name	O	1		Used
320	N3	Address Information	O	2		Used
330	N4	Geographic Location	O	1		Used

**Comments:**

- 1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
- 2. N105 and N106 further define the type of entity in N101.

# N1 Name

<b>Pos: 300</b>	<b>Max: 1</b>
<b>Heading - Optional</b>	
<b>Loop: N1</b>	<b>Elements: 4</b>

**User Option (Usage):** Used

**Purpose:** To identify a party by type of organization, name, and code

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	<b>Entity Identifier Code</b>	M	ID	2/3	Must use

**Description:** Code identifying an organizational entity, a physical location, property or an individual

**CodeList Summary** (Total Codes: 1312, Included: 3)

### Code Name

BY Buying Party (Purchaser)

#### **General Mills Note:**

*BY party will identify General Mills as purchaser of items on this purchase order*

SF Ship From

#### **General Mills Note:**

*Ship from location will reflect either the site from which items are being sourced or the corporate office of the supplier.*

ST Ship To

#### **General Mills Note:**

*Ship to location will be the location receiving the product associated with this PO.*

N102	93	<b>Name</b>	C	AN	1/60	Used
------	----	-------------	---	----	------	------

**Description:** Free-form name

N103	66	<b>Identification Code Qualifier</b>	C	ID	1/2	Used
------	----	--------------------------------------	---	----	-----	------

**Description:** Code designating the system/method of code structure used for Identification Code (67)

**CodeList Summary** (Total Codes: 215, Included: 2)

### Code Name

9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix

92 Assigned by Buyer or Buyer's Agent

N104	67	<b>Identification Code</b>	C	AN	2/80	Used
------	----	----------------------------	---	----	------	------

**Description:** Code identifying a party or other code

## Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

## Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

# N3 Address Information

Pos: 320	Max: 2
Heading - Optional	
Loop: N1	Elements: 1

User Option (Usage): Used  
Purpose: To specify the location of the named party

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N301	166	Address Information	M	AN	1/55	Must use
Description: Address information						

# N4 Geographic Location

<b>Pos: 330</b>	<b>Max: 1</b>
<b>Heading - Optional</b>	
<b>Loop: N1</b>	<b>Elements: 3</b>

**User Option (Usage):** Used

**Purpose:** To specify the geographic place of the named party

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	<b>City Name</b>	O	AN	2/30	Used
		<b>Description:</b> Free-form text for city name				
N402	156	<b>State or Province Code</b>	O	ID	2/2	Used
		<b>Description:</b> Code (Standard State/Province) as defined by appropriate government agency				
N403	116	<b>Postal Code</b>	O	ID	3/15	Used
		<b>Description:</b> Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				

## Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

## Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

# Loop Baseline Item Data

Pos: 010	Repeat: 100000
Optional	
Loop: PO1	Elements: N/A

User Option (Usage): Used  
Purpose: To specify basic and most frequently used line item data

## Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
010	PO1	Baseline Item Data	O	1		Used
050		Loop PID	O		1000	Used
350		Loop N9	O		1000	Used

## Comments:

- 1. See the Data Element Dictionary for a complete list of IDs.
- 2. PO101 is the line item identification.
- 3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.



# PO1 Baseline Item Data

Pos: 010	Max: 1
Detail - Optional	
Loop: PO1	Elements: 4

**User Option (Usage):** Used

**Purpose:** To specify basic and most frequently used line item data

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO102	330	Quantity Ordered	C	R0	1/15	Used

**Description:** Quantity ordered

PO103	355	Unit or Basis for Measurement Code	O	ID	2/2	Used
-------	-----	------------------------------------	---	----	-----	------

**Description:** Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

**General Mills Note:** These codes represent the most commonly used Base Unit Of Measurement Codes within General Mills.

**CodeList Summary** (Total Codes: 794, Included: 12)

### Code Name

BG	Bag
CA	Case
CN	Can
CW	Hundred Pounds (CWT)
DR	Drum
EA	Each
FT	Foot
GA	Gallon
IN	Inch
LB	Pound
PL	Pallet/Unit Load
RL	Roll

PO106	235	Product/Service ID Qualifier	C	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

**Description:** Code identifying the type/source of the descriptive number used in Product/Service ID (234)

**CodeList Summary** (Total Codes: 477, Included: 1)

### Code Name

IN	Buyer's Item Number
----	---------------------

**General Mills Note:**  
General Mills Material Number.

PO107	234	Product/Service ID	C	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

**Description:** Identifying number for a product or service

## Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.

9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

**Comments:**

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

**General Mills Note:**

*This segment is used to identify the product and quantity being shipped or proposed by the manufacturer.*

# Loop Product/Item Description

Pos: 050	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

**User Option (Usage):** Used

**Purpose:** To describe a product or process in coded or free-form format

## Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
050	PID	Product/Item Description	O	1		Used

## Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

## Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

# PID Product/Item Description

Pos: 050	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

**User Option (Usage):** Used

**Purpose:** To describe a product or process in coded or free-form format

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

**Description:** Code indicating the format of a description

**CodeList Summary** (Total Codes: 3, Included: 1)

<u>Code</u>	<u>Name</u>
F	Free-form

PID05	352	Description	C	AN	1/80	Used
-------	-----	-------------	---	----	------	------

**Description:** A free-form description to clarify the related data elements and their content

## Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

## Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

## Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

# Loop Reference Identification

Pos: 350	Repeat: 1000
Optional	
Loop: N9	Elements: N/A

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

## Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
350	N9	Reference Identification	O	1		Used
360	MSG	Message Text	O	1000		Used

## Semantics:

- 1. N906 reflects the time zone which the time reflects.

# N9 Reference Identification

Pos: 350	Max: 1
Detail - Optional	
Loop: N9	Elements: 2

**User Option (Usage):** Used

**Purpose:** To transmit identifying information as specified by the Reference Identification Qualifier

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use
<b>Description:</b> Code qualifying the Reference Identification						
<b>CodeList Summary</b> (Total Codes: 1503, Included: 1)						
<b>Code Name</b>						
BV Purchase Order Line Item Identifier (Buyer)						
N902	127	Reference Identification	C	AN	1/30	Used
<b>Description:</b> Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						

## Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

## Semantics:

1. N906 reflects the time zone which the time reflects.

# MSG Message Text

Pos: 360	Max: 1000
Detail - Optional	
Loop: N9	Elements: 1

**User Option (Usage):** Used

**Purpose:** To provide a free-form format that allows the transmission of text information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text	M	AN	1/264	Must use

**Description:** Free-form message text

**General Mills Note:** *If populated in our application, we will include delivery time here.*

## Syntax Rules:

1. C0302 - If MSG03 is present, then MSG02 is required.

## Semantics:

1. MSG03 is the number of lines to advance before printing.

## Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

# Loop Transaction Totals

Pos: 010	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

User Option (Usage): Used  
Purpose: To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		Used

Comments:

- 1. This segment is intended to provide hash totals to validate transaction completeness and correctness.



# CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: CTT	Elements: 1

**User Option (Usage):** Used

**Purpose:** To transmit a hash total for a specific element in the transaction set

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

**Description:** Total number of line items in the transaction set

**General Mills Note:** CTT01 contains the number of PO1 segments present in the transaction set.

## Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

## Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

# SE Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

## Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

## Comments:

- 1. SE is the last segment of each transaction set.

# GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To indicate the end of a functional group and to provide control information

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use

**Description:** Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element

**General Mills Note:** *The count of ST segments within the group.*

GE02	28	Group Control Number	M	N0	1/9	Must use
------	----	----------------------	---	----	-----	----------

**Description:** Assigned number originated and maintained by the sender

**General Mills Note:** *This must be the same number as is in the GS segment (GS06) for the group.*

## Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

## Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

# IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

**User Option (Usage):** Must use

**Purpose:** To define the end of an interchange of zero or more functional groups and interchange-related control segments

## Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use

**Description:** A count of the number of functional groups included in an interchange

**General Mills Note:** IEA01 contains the count of GS segments within the transmission.

IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
-------	-----	----------------------------	---	----	-----	----------

**Description:** A control number assigned by the interchange sender

**General Mills Note:** IEA02 must be the same number as in the ISA segment (ISA13) for the transmission.