



**General
Mills**

**Making Food
People Love**

EDI 990 Response to a Load Tender

X12/Version 4010/990: Response to a Load Tender

Company:

General Mills

Modified:

9/3/2020

Notes:

**This EDI 990 Spec is used for
General Mills Truckload and
LTL Freight Carriers**

Table of Contents

990 Response to a Load Tender **1**

ISA Interchange Control Header **2**

GS Functional Group Header **4**

ST Transaction Set Header **5**

B1 Beginning Segment for Booking or Pick-up/Delivery **6**

N9 Reference Identification **7**

L9 Charge Detail **8**

K1 Remarks **9**

SE Transaction Set Trailer **10**

GE Functional Group Trailer **11**

IEA Interchange Control Trailer **12**

990 Response to a Load Tender

Functional Group=GF

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Response to a Load Tender Transaction Set (990) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide general information relative to a specific shipment. The Response to a Load Tender is used as the response to a Motor Carrier Shipment Information Transaction Set (204) which has been used as a load tender.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
10	ST	Transaction Set Header	M	1			Must use
20	B1	Beginning Segment for Booking or Pick-up/Delivery	M	1			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
30	N9	Reference Identification	O	1			Used

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
40	L9	Charge Detail	O	40			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
60	K1	Remarks	O	10			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
70	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

General Mills Note:

L9 segment is required when responding to a BROADCAST QUOTE Tender ("BRDCSTQUOT" in L1101 of EDI 204 Load Tender). When the L9 segment is included in a response to a non-Broadcast Quote tender, it is ignored.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Authorization Information All valid standard codes are used. (Total Codes: 7)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Security Information All valid standard codes are used. (Total Codes: 2)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used. (Total Codes: 37)						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified CodeList Summary (Total Codes: 38, Included: 1) <u>Code</u> <u>Name</u> 08 UCC EDI Communications ID (Comm ID)						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them General Mills Note: <i>General Mills ID = 9251190000</i>						
ISA09	I08	Interchange Date	M	DT	6/6	Must use
Description: Date of the interchange						
ISA10	I09	Interchange Time	M	TM	4/4	Must use
Description: Time of the interchange						
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used. (Total Codes: 1)						
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
Description: Code specifying the version number of the interchange control segments CodeList Summary (Total Codes: 14, Included: 1) <u>Code</u> <u>Name</u> 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997						
ISA13	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
Description: Code sent by the sender to request an interchange acknowledgment (TA1) All valid standard codes are used. (Total Codes: 2)						
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information CodeList Summary (Total Codes: 3, Included: 1) <u>Code</u> <u>Name</u> P Production Data						
ISA16	I15	Component Element Separator	M		1/1	Must use
Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator						

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use

Description: Code identifying a group of application related transaction sets

CodeList Summary (Total Codes: 240, Included: 1)

Code Name

GF Response to a Load Tender (990)

GS02	142	Application Sender's Code	M	AN	2/15	Must use
------	-----	----------------------------------	---	----	------	----------

Description: Code identifying party sending transmission; codes agreed to by trading partners

GS03	124	Application Receiver's Code	M	AN	2/15	Must use
------	-----	------------------------------------	---	----	------	----------

Description: Code identifying party receiving transmission; codes agreed to by trading partners

General Mills Note:

General Mills ID = 6125404455

GS04	373	Date	M	DT	8/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

GS05	337	Time	M	TM	4/8	Must use
------	-----	-------------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

GS06	28	Group Control Number	M	N0	1/9	Must use
------	----	-----------------------------	---	----	-----	----------

Description: Assigned number originated and maintained by the sender

GS07	455	Responsible Agency Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code identifying the issuer of the standard; this code is used in conjunction with Data Element 480

CodeList Summary (Total Codes: 2, Included: 1)

Code Name

X Accredited Standards Committee X12

GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
------	-----	---	---	----	------	----------

Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed

CodeList Summary (Total Codes: 39, Included: 1)

Code Name

004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997

ST Transaction Set Header

Pos: 10	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use				
Description: Code uniquely identifying a Transaction Set										
CodeList Summary (Total Codes: 298, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>990</td><td>Response To a Load Tender</td></tr></table>							<u>Code</u>	<u>Name</u>	990	Response To a Load Tender
<u>Code</u>	<u>Name</u>									
990	Response To a Load Tender									
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use				
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set										

B1 Beginning Segment for Booking or Pick-up/Delivery

Pos: 20	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
B101	140	Standard Carrier Alpha Code	O	ID	2/4	Must use
Description: Standard Carrier Alpha Code General Mills Note: <i>Must match SCAC in B202 element of EDI 204 Load Tender</i>						
B102	145	Shipment Identification Number	M	AN	1/30	Must use
Description: Identification number assigned to the shipment by the shipper that uniquely identifies the shipment from origin to ultimate destination and is not subject to modification; (Does not contain blanks or special characters) General Mills Note: <i>General Mills 10 digit Shipment Number (from B204 element of EDI 204 Load Tender)</i>						
B103	373	Date	O	DT	8/8	Used
Description: Date expressed as CCYYMMDD						
B104	558	Reservation Action Code	O	ID	1/1	Must use
Description: Code identifying action on reservation or offering General Mills Note: <i>Only codes listed (A or D) should be sent in the B104 element. However if "U" is sent in response to an Update Tender, it will be processed - as an Accept.</i>						

CodeList Summary (Total Codes: 7, Included: 2)

Code Name

A Reservation Accepted

General Mills Note:

Send A to Accept the Load Tender offer

D Reservation Cancelled

General Mills Note:

Send D to Decline the Load Tender offer

General Mills Note:

Only codes listed (A or D) should be sent in the B104 element.

However if "U" is sent in the B104 when responding to an Update Tender, it will be processed - as an Accept.

N9 Reference Identification

Pos: 30	Max: 1
Detail - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Used

Description: Code qualifying the Reference Identification

General Mills Note:

Use code CN here when providing Carrier PRO Number in the N902 element.

CodeList Summary (Total Codes: 1503, Included: 1)

Code Name

CN Carrier's Reference Number (PRO/Invoice)

N902	127	Reference Identification	O	AN	1/30	Used
------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

General Mills Note:

When N901 = CN, provide Carrier PRO number here.

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

General Mills Note:

Do Not send this segment when Load Tender offer is being declined (when B104 = D).

L9 Charge Detail

Pos: 40	Max: 40
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To specify special charge code and the associated monetary amount

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
L901	150	Special Charge or Allowance Code	M	ID	3/3	Must use

Description: Code identifying type of special charge or allowance

General Mills Note:

Do Not use codes in the L901 element other than those listed!

CodeList Summary (Total Codes: 1073, Included: 2)

Code Name

150 Canadian Currency

Description: Use code 150 when monetary amount in L902 is represented in Canadian Dollars.

TCM Transportation Charge - US Currency

Description: Use code TCM when monetary amount in L902 is represented in US Dollars.

L902	782	Monetary Amount	M	R	1/18	Must use
------	-----	-----------------	---	---	------	----------

Description: Monetary amount

General Mills Note:

Include decimal.

General Mills Note:

The L9 segment must contain a rate quote for the Broadcast Quote Load Tender Offer ("BRDCSTQUOT" in the L1101 of EDI 204)

This segment is **REQUIRED** when responding to a **Broadcast Quote Tender** ("BRDCSTQUOT" in L1101 of EDI 204 Load Tender).

This segment is ignored if it is included in a response to a non-Broadcast Quote tender.

Do Not use codes in the L901 element other than those listed (150for Canadian Dollars or TCMfor US Dollars)!

K1 Remarks

Pos: 60	Max: 10
Detail - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used
Purpose: To transmit information in a free-form format for comment or special instruction

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
K101	61	Free-Form Message	M	AN	1/30	Used
Description: Free-form information						
General Mills Note: Remarks are usually sent by the carrier when the carrier declines a tendered load. These remarks would indicate why the load was declined. Remarks are allowed when the load is accepted as well.						
K102	61	Free-Form Message	O	AN	1/30	Used
Description: Free-form information						

SE Transaction Set Trailer

Pos: 70	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						