



**General
Mills**

**Making Food
People Love**

850 Purchase Order

X12/V4010/850: 850 Purchase Order

Company:

General Mills

Modified:

1/11/2018

Notes:

Table of Contents

850	Purchase Order	1
ISA	Interchange Control Header	3
GS	Functional Group Header	5
ST	Transaction Set Header	7
BEG	Beginning Segment for Purchase Order	8
CUR	Currency	9
REF	Reference Identification	10
PER	Administrative Communications Contact	11
FOB	F.O.B. Related Instructions	12
ITD	Terms of Sale/Deferred Terms of Sale	14
N9	Loop Reference Identification	15
N9	Reference Identification	16
MSG	Message Text	17
N1	Loop Name	18
N1	Name	19
N2	Additional Name Information	20
N3	Address Information	21
N4	Geographic Location	22
PO1	Loop Baseline Item Data	23
PO1	Baseline Item Data	24
PID	Loop Product/Item Description	27
PID	Product/Item Description	28
REF	Reference Identification	29
SAC	Loop Service, Promotion, Allowance, or Charge Information	30
SAC	Service, Promotion, Allowance, or Charge Information	31
DTM	Date/Time Reference	33
TD5	Carrier Details (Routing Sequence/Transit Time)	34
PKG	Loop Marking, Packaging, Loading	35
PKG	Marking, Packaging, Loading	36
N9	Loop Reference Identification	37
N9	Reference Identification	38
MSG	Message Text	39
N1	Loop Name	40
N1	Name	41
N2	Additional Name Information	42
N3	Address Information	43
N4	Geographic Location	44
CTT	Loop Transaction Totals	45
CTT	Transaction Totals	46
SE	Transaction Set Trailer	47
GE	Functional Group Trailer	48
IEA	Interchange Control Trailer	49

850 Purchase Order

Functional Group=**PO**

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Purchase Order Transaction Set (850) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the placement of purchase orders for goods and services. This transaction set should not be used to convey purchase order changes or purchase order acknowledgment information.

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Must use
	GS	Functional Group Header	M	1			Must use

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BEG	Beginning Segment for Purchase Order	M	1			Must use
040	CUR	Currency	O	1			Must use
050	REF	Reference Identification	O	>1			Used
060	PER	Administrative Communications Contact	O	3			Must use
080	FOB	F.O.B. Related Instructions	O	>1			Used
130	ITD	Terms of Sale/Deferred Terms of Sale	O	>1			Must use

<u>LOOP ID - N9</u>			<u>1000</u>				
295	N9	Reference Identification	O	1			Must use
300	MSG	Message Text	O	1000			Must use
<u>LOOP ID - N1</u>			<u>200</u>				
310	N1	Name	O	1			Must use
320	N2	Additional Name Information	O	2			Used
330	N3	Address Information	O	2			Used
340	N4	Geographic Location	O	>1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - PO1</u>			<u>100000</u>			<u>N2/010L</u>	
010	PO1	Baseline Item Data	M	1		N2/010	Must use
<u>LOOP ID - PID</u>			<u>1000</u>				
050	PID	Product/Item Description	O	1			Must use
100	REF	Reference Identification	O	>1			Must use
<u>LOOP ID - SAC</u>			<u>25</u>				
130	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
210	DTM	Date/Time Reference	O	10			Must use
250	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12			Used
<u>LOOP ID - PKG</u>			<u>200</u>				
305	PKG	Marking, Packaging, Loading	O	1			Must use
<u>LOOP ID - N9</u>			<u>1000</u>				
330	N9	Reference Identification	O	1			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
340	MSG	Message Text	O	1000			Must use
LOOP ID - N1					200		
350	N1	Name	O	1			Must use
360	N2	Additional Name Information	O	2			Used
370	N3	Address Information	O	2			Used
380	N4	Geographic Location	O	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - CTT					1	N3/010L	
010	CTT	Transaction Totals	O	1		N3/010	Must use
030	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Must use
	IEA	Interchange Control Trailer	M	1			Must use

Notes:

2/010L PO102 is required.

2/010 PO102 is required.

3/010L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

3/010 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

ISA Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Must use

Purpose: To start and identify an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Authorization Information						
CodeList Summary (Total Codes: 7, Included: 1)						
Code Name						
00 No Authorization Information Present (No Meaningful Information in I02)						
ISA02	I02	Authorization Information	M	AN	10/10	Must use
Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)						
ISA03	I03	Security Information Qualifier	M	ID	2/2	Must use
Description: Code to identify the type of information in the Security Information						
CodeList Summary (Total Codes: 2, Included: 1)						
Code Name						
00 No Security Information Present (No Meaningful Information in I04)						
ISA04	I04	Security Information	M	AN	10/10	Must use
Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)						
ISA05	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified						
All valid standard codes are used. (Total Codes: 38)						
ISA06	I06	Interchange Sender ID	M	AN	15/15	Must use
Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element						
ISA07	I05	Interchange ID Qualifier	M	ID	2/2	Must use
Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified						
All valid standard codes are used. (Total Codes: 38)						
ISA08	I07	Interchange Receiver ID	M	AN	15/15	Must use
Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them						
ISA09	I08	Interchange Date	M	DT	6/6	Must use
Description: Date of the interchange						
ISA10	I09	Interchange Time	M	TM	4/4	Must use
Description: Time of the interchange						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA11	I10	Interchange Control Standards Identifier	M	ID	1/1	Must use
Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer All valid standard codes are used. (Total Codes: 1)						
ISA12	I11	Interchange Control Version Number	M	ID	5/5	Must use
Description: Code specifying the version number of the interchange control segments CodeList Summary (Total Codes: 13, Included: 1) <u>Code</u> <u>Name</u> 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997						
ISA13	I12	Interchange Control Number	M	NO	9/9	Must use
Description: A control number assigned by the interchange sender						
ISA14	I13	Acknowledgment Requested	M	ID	1/1	Must use
Description: Code sent by the sender to request an interchange acknowledgment (TA1) All valid standard codes are used. (Total Codes: 2)						
ISA15	I14	Usage Indicator	M	ID	1/1	Must use
Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information CodeList Summary (Total Codes: 3, Included: 2) <u>Code</u> <u>Name</u> P Production Data T Test Data						
ISA16	I15	Component Element Separator	M		1/1	Must use
Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator						

General Mills Note:

General Mills Production ID's are:
ISA Qualifier: 08
ISA: 9251190000

GS Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Must use

Purpose: To indicate the beginning of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code	M	ID	2/2	Must use
Description: Code identifying a group of application related transaction sets						
CodeList Summary (Total Codes: 225, Included: 1)						
<u>Code</u> <u>Name</u>						
PO Purchase Order (850)						
GS02	142	Application Sender's Code	M	AN	2/15	Must use
Description: Code identifying party sending transmission; codes agreed to by trading partners						
GS03	124	Application Receiver's Code	M	AN	2/15	Must use
Description: Code identifying party receiving transmission; codes agreed to by trading partners						
GS04	373	Date	M	DT	8/8	Must use
Description: Date expressed as CCYYMMDD						
GS05	337	Time	M	TM	4/8	Must use
Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)						
GS06	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						
GS07	455	Responsible Agency Code	M	ID	1/2	Must use
Description: Code used in conjunction with Data Element 480 to identify the issuer of the standard						
CodeList Summary (Total Codes: 2, Included: 1)						
<u>Code</u> <u>Name</u>						
X Accredited Standards Committee X12						
GS08	480	Version / Release / Industry Identifier Code	M	AN	1/12	Must use
Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed						
CodeList Summary (Total Codes: 32, Included: 1)						
<u>Code</u> <u>Name</u>						
004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997						

Semantics:

1. GS04 is the group date.
2. GS05 is the group time.

3. The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

General Mills Note:

General Mills production ID is:
6125404455

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use				
Description: Code uniquely identifying a Transaction Set										
CodeList Summary (Total Codes: 298, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>850</td><td>Purchase Order</td></tr></table>							<u>Code</u>	<u>Name</u>	850	Purchase Order
<u>Code</u>	<u>Name</u>									
850	Purchase Order									
ST02	329	Transaction Set Control Number	M	AN	4/9	Must use				
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set										

Semantics:

- 1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BEG Beginning Segment for Purchase Order

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
BEG01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

Description: Code identifying purpose of transaction set

CodeList Summary (Total Codes: 65, Included: 1)

Code Name

00 Original

BEG02	92	Purchase Order Type Code	M	ID	2/2	Must use
-------	----	--------------------------	---	----	-----	----------

Description: Code specifying the type of Purchase Order

CodeList Summary (Total Codes: 69, Included: 2)

Code Name

BK Blanket Order (Quantity Firm)

SA Stand-alone Order

BEG03	324	Purchase Order Number	M	AN	1/22	Must use
-------	-----	-----------------------	---	----	------	----------

Description: Identifying number for Purchase Order assigned by the orderer/purchaser

General Mills Note:

General Mills format for PO Number = 8 digits.

BEG05	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

Semantics:

1. BEG05 is the date assigned by the purchaser to purchase order.

CUR Currency

Pos: 040	Max: 1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify the currency (dollars, pounds, francs, etc.) used in a transaction

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CUR01	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 1)

Code Name

BY Buying Party (Purchaser)

CUR02	100	Currency Code	M	ID	3/3	Must use
-------	-----	----------------------	---	----	-----	----------

Description: Code (Standard ISO) for country in whose currency the charges are specified

General Mills Note:

USD = US Dollars

CAD = Canadian Dollars

Syntax Rules:

1. C0807 - If CUR08 is present, then CUR07 is required.
2. C0907 - If CUR09 is present, then CUR07 is required.
3. L101112 - If CUR10 is present, then at least one of CUR11 or CUR12 is required.
4. C1110 - If CUR11 is present, then CUR10 is required.
5. C1210 - If CUR12 is present, then CUR10 is required.
6. L131415 - If CUR13 is present, then at least one of CUR14 or CUR15 is required.
7. C1413 - If CUR14 is present, then CUR13 is required.
8. C1513 - If CUR15 is present, then CUR13 is required.
9. L161718 - If CUR16 is present, then at least one of CUR17 or CUR18 is required.
10. C1716 - If CUR17 is present, then CUR16 is required.
11. C1816 - If CUR18 is present, then CUR16 is required.
12. L192021 - If CUR19 is present, then at least one of CUR20 or CUR21 is required.
13. C2019 - If CUR20 is present, then CUR19 is required.
14. C2119 - If CUR21 is present, then CUR19 is required.

Comments:

1. See Figures Appendix for examples detailing the use of the CUR segment.

REF Reference Identification

Pos: 050	Max: >1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used
Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use				
Description: Code qualifying the Reference Identification										
CodeList Summary (Total Codes: 1503, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>FR</td><td>Freight Required</td></tr></table>							<u>Code</u>	<u>Name</u>	FR	Freight Required
<u>Code</u>	<u>Name</u>									
FR	Freight Required									
REF02	127	Reference Identification	X	AN	1/30	Used				
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier										
General Mills Note: <i>This description will read FREIGHT REQUIRED when the Suppling Partner is participating in the General Mills Inbound Freight Program.</i>										

Syntax Rules:

- 1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

- 1. REF04 contains data relating to the value cited in REF02.

General Mills Note:

This segment will only be sent when the Suppling Partner is participating in the General Mills Inbound Freight Program.

PER Administrative Communications Contact

Pos: 060	Max: 3
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use
Description: Code identifying the major duty or responsibility of the person or group named						
CodeList Summary (Total Codes: 230, Included: 2)						
<u>Code</u> <u>Name</u>						
BD Buyer Name or Department						
OC Order Contact						
PER02	93	Name	O	AN	1/60	Must use
Description: Free-form name						
PER03	365	Communication Number Qualifier	X	ID	2/2	Must use
Description: Code identifying the type of communication number						
CodeList Summary (Total Codes: 40, Included: 1)						
<u>Code</u> <u>Name</u>						
TE Telephone						
PER04	364	Communication Number	X	AN	1/80	Must use
Description: Complete communications number including country or area code when applicable						

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

FOB F.O.B. Related Instructions

Pos: 080	Max: >1
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Used

Purpose: To specify transportation instructions relating to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>														
FOB01	146	Shipment Method of Payment	M	ID	2/2	Must use														
Description: Code identifying payment terms for transportation charges																				
CodeList Summary (Total Codes: 28, Included: 5)																				
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>BP</td><td>Paid by Buyer</td></tr><tr><td colspan="2">Description: The buyer agrees to the transportation payment term requiring the buyer to pay transportation charges to a specified location (origin or destination location)</td></tr><tr><td>CC</td><td>Collect</td></tr><tr><td>MX</td><td>Mixed</td></tr><tr><td>PC</td><td>Prepaid but Charged to Customer</td></tr><tr><td>PP</td><td>Prepaid (by Seller)</td></tr></table>							<u>Code</u>	<u>Name</u>	BP	Paid by Buyer	Description: The buyer agrees to the transportation payment term requiring the buyer to pay transportation charges to a specified location (origin or destination location)		CC	Collect	MX	Mixed	PC	Prepaid but Charged to Customer	PP	Prepaid (by Seller)
<u>Code</u>	<u>Name</u>																			
BP	Paid by Buyer																			
Description: The buyer agrees to the transportation payment term requiring the buyer to pay transportation charges to a specified location (origin or destination location)																				
CC	Collect																			
MX	Mixed																			
PC	Prepaid but Charged to Customer																			
PP	Prepaid (by Seller)																			
FOB02	309	Location Qualifier	X	ID	1/2	Must use														
Description: Code identifying type of location																				
CodeList Summary (Total Codes: 172, Included: 3)																				
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>DE</td><td>Destination (Shipping)</td></tr><tr><td>OA</td><td>Origin (After Loading on Equipment)</td></tr><tr><td>OR</td><td>Origin (Shipping Point)</td></tr></table>							<u>Code</u>	<u>Name</u>	DE	Destination (Shipping)	OA	Origin (After Loading on Equipment)	OR	Origin (Shipping Point)						
<u>Code</u>	<u>Name</u>																			
DE	Destination (Shipping)																			
OA	Origin (After Loading on Equipment)																			
OR	Origin (Shipping Point)																			
FOB03	352	Description	O	AN	1/80	Must use														
Description: A free-form description to clarify the related data elements and their content																				
General Mills Note: GMI length = 40																				
FOB06	309	Location Qualifier	X	ID	1/2	Used														
Description: Code identifying type of location																				
CodeList Summary (Total Codes: 172, Included: 1)																				
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>ZZ</td><td>Mutually Defined</td></tr></table>							<u>Code</u>	<u>Name</u>	ZZ	Mutually Defined										
<u>Code</u>	<u>Name</u>																			
ZZ	Mutually Defined																			
FOB07	352	Description	O	AN	1/80	Used														
Description: A free-form description to clarify the related data elements and their content																				
General Mills Note: GMI length = 28 characters for destination.																				

Syntax Rules:

1. C0302 - If FOB03 is present, then FOB02 is required.
2. C0405 - If FOB04 is present, then FOB05 is required.
3. C0706 - If FOB07 is present, then FOB06 is required.
4. C0809 - If FOB08 is present, then FOB09 is required.

Semantics:

1. FOB01 indicates which party will pay the carrier.
2. FOB02 is the code specifying transportation responsibility location.
3. FOB06 is the code specifying the title passage location.
4. FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 130	Max: >1
Heading - Optional	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD02	333	Terms Basis Date Code	O	ID	1/2	Must use
Description: Code identifying the beginning of the terms period						
CodeList Summary (Total Codes: 17, Included: 1)						
Code Name						
3 Invoice Date						
ITD03	338	Terms Discount Percent	O	R	1/6	Used
Description: Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date						
ITD05	351	Terms Discount Days Due	X	N0	1/3	Used
Description: Number of days in the terms discount period by which payment is due if terms discount is earned						
ITD07	386	Terms Net Days	O	N0	1/3	Used
Description: Number of days until total invoice amount is due (discount not applicable)						

Syntax Rules:

1. L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
2. L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.
3. L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

General Mills Note:

Two ITD segments may be sent. The first segment identifies the discount for paying early (ITD02, ITD03, and ITD05). The second segment identifies the net days without the discount (ITD02 and ITD07).

Loop Reference Identification

Pos: 295	Repeat: 1000
Optional	
Loop: N9	Elements: N/A

User Option (Usage): Must use
Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
295	N9	Reference Identification	O	1		Must use
300	MSG	Message Text	O	1000		Must use

N9 Reference Identification

Pos: 295	Max: 1
Heading - Optional	
Loop: N9	Elements: 3

User Option (Usage): Must use

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use
Description: Code qualifying the Reference Identification						
CodeList Summary (Total Codes: 1503, Included: 2)						
Code Name						
55 Sequence Number						
ME Message Address or ID						
N902	127	Reference Identification	X	AN	1/30	Must use
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier						
N903	369	Free-form Description	X	AN	1/45	Must use
Description: Free-form descriptive text						

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

General Mills Note:

The first N9/MSG loop has standard messages related to terms and conditions as well as environmental standards. If a second N9 loop exists, it will contain other messages related to the order. The N9/ME loop will contain messages related to shipping instructions.

MSG Message Text

Pos: 300	Max: 1000
Heading - Optional	
Loop: N9	Elements: 1

User Option (Usage): Must use

Purpose: To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text	M	AN	1/264	Must use

Description: Free-form message text

General Mills Note:

General Mills maximum = 72.

Syntax Rules:

1. C0302 - If MSG03 is present, then MSG02 is required.

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

Loop Name

Pos: 310	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Must use
Purpose: To identify a party by type of organization, name, and code

Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
310	N1	Name	O	1		Must use
320	N2	Additional Name Information	O	2		Used
330	N3	Address Information	O	2		Used
340	N4	Geographic Location	O	>1		Used

N1 Name

Pos: 310	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 3)

Code Name

BY Buying Party (Purchaser)
SE Selling Party
SF Ship From

N102	93	Name	X	AN	1/60	Must use
------	----	-------------	---	----	------	----------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Used
------	----	--------------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 215, Included: 1)

Code Name

92 Assigned by Buyer or Buyer's Agent

N104	67	Identification Code	X	AN	2/80	Used
------	----	----------------------------	---	----	------	------

Description: Code identifying a party or other code

General Mills Note:

Supplier: For the most updated Ship To address information create your master list based on EDI data sent in N1, N2, N3 and N4

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

General Mills Note:

*If N101= BY, General Mills will send '0001' in the N104 to identify U.S. or '0002' to identify Canada
If N101 = SE, General Mills will send our vendor number in the N104 associated with this Purchase Order.
If N101 = SF, General Mills will send our 10-digit number assigned for the partner's ShipFrom location.*

N2 Additional Name Information

Pos: 320	Max: 2
Heading - Optional	
Loop: N1	Elements: 1

User Option (Usage): Used
Purpose: To specify additional names or those longer than 35 characters in length

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use
Description: Free-form name						

N3 Address Information

Pos: 330	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used
Purpose: To specify the location of the named party

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 340	Max: >1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Must use
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Must use
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Must use
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Must use
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Baseline Item Data

Pos: 010	Repeat: 100000
Mandatory	
Loop: PO1	Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	PO1	Baseline Item Data	M	1		Must use
050		Loop PID	O		1000	Must use
100	REF	Reference Identification	O	>1		Must use
130		Loop SAC	O		25	Used
210	DTM	Date/Time Reference	O	10		Must use
250	TD5	Carrier Details (Routing Sequence/Transit Time)	O	12		Used
305		Loop PKG	O		200	Used
330		Loop N9	O		1000	Used
350		Loop N1	O		200	Used

PO1 Baseline Item Data

Pos: 010	Max: 1
Detail - Mandatory	
Loop: PO1	Elements: 13

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification	O	AN	1/20	Must use
Description: Alphanumeric characters assigned for differentiation within a transaction set General Mills Note: <i>General Mills PO Line Item Number = 7 digits</i>						
PO102	330	Quantity Ordered	X	R	1/15	Must use
Description: Quantity ordered General Mills Note: <i>General Mills maximum = 99999999.9</i>						
PO103	355	Unit or Basis for Measurement Code	O	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken General Mills Note: <i>General Mills typically uses the following:</i> CodeList Summary (Total Codes: 794, Included: 2) <u>Code</u> <u>Name</u> EA Each LB Pound						
PO104	212	Unit Price	X	R	1/17	Must use
Description: Price per unit of product, service, commodity, etc.						
PO105	639	Basis of Unit Price Code	O	ID	2/2	Must use
Description: Code identifying the type of unit price for an item General Mills Note: <i>This data element is used to clarify or alter the basis of unit price. The unit price expressed in PO104 may be the same terms as the unit of measure in the PO103, unless otherwise specified in PO105. For example, unit of measure equals EA but priced per hundred.</i> <i>General Mills typically uses the following:</i> CodeList Summary (Total Codes: 91, Included: 5) <u>Code</u> <u>Name</u> HP Price per Hundred PE Price per Each PN Price per Ten TP Price per Thousand TT Price Per 10,000						
PO106	235	Product/Service ID Qualifier	X	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234) CodeList Summary (Total Codes: 477, Included: 1)						

		<u>Code</u> <u>Name</u>				
		BP Buyer's Part Number				
PO107	234	Product/Service ID	X	AN	1/48	Must use
		Description: Identifying number for a product or service				
		General Mills Note:				
		<i>General Mills Material Numbers = 10 digits. For Trial Orders the value = NoMaterial.</i>				
PO108	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 477, Included: 1)				
		<u>Code</u> <u>Name</u>				
		MG Manufacturer's Part Number				
PO109	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO110	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 477, Included: 1)				
		<u>Code</u> <u>Name</u>				
		MF Manufacturer				
PO111	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
PO112	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 477, Included: 1)				
		<u>Code</u> <u>Name</u>				
		VN Vendor's (Seller's) Item Number				
PO113	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.
9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Loop Product/Item Description

Pos: 050	Repeat: 1000
Optional	
Loop: PID	Elements: N/A

User Option (Usage): Must use
Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
050	PID	Product/Item Description	O	1		Must use

PID Product/Item Description

Pos: 050	Max: 1
Detail - Optional	
Loop: PID	Elements: 2

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

<u>Code</u>	<u>Name</u>
F	Free-form

PID05	352	Description	X	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

General Mills Note:

General Mills will send two PID segments where PID01 = 'F': one for material description and one for style description.

REF Reference Identification

Pos: 100	Max: >1
Detail - Optional	
Loop: PO1	Elements: 2

User Option (Usage): Must use
Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>										
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use										
Description: Code qualifying the Reference Identification																
CodeList Summary (Total Codes: 1503, Included: 4)																
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>C7</td><td>Contract Line Item Number</td></tr><tr><td>CT</td><td>Contract Number</td></tr><tr><td>DG</td><td>Drawing Number</td></tr><tr><td>S3</td><td>Specification Number</td></tr></table>							<u>Code</u>	<u>Name</u>	C7	Contract Line Item Number	CT	Contract Number	DG	Drawing Number	S3	Specification Number
<u>Code</u>	<u>Name</u>															
C7	Contract Line Item Number															
CT	Contract Number															
DG	Drawing Number															
S3	Specification Number															
REF02	127	Reference Identification	X	AN	1/30	Must use										
Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier																

Syntax Rules:

- 1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

- 1. REF04 contains data relating to the value cited in REF02.

Loop Service, Promotion, Allowance, or Charge Information

Pos: 130	Repeat: 25
Optional	
Loop: SAC	Elements: N/A

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
130	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 130	Max: 1
Detail - Optional	
Loop: SAC	Elements: 3

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use

Description: Code which indicates an allowance or charge for the service specified

CodeList Summary (Total Codes: 7, Included: 2)

Code Name

A	Allowance
C	Charge

SAC02	1300	Service, Promotion, Allowance, or Charge Code	X	ID	4/4	Used
-------	------	---	---	----	-----	------

Description: Code identifying the service, promotion, allowance, or charge

CodeList Summary (Total Codes: 1053, Included: 15)

Code Name

A172	Administrative
A730	Brokerage or Duty
D240	Freight
D270	Fuel Surcharge
D870	Inspection
F180	Pallet
F750	Processing Charge
F920	Quantity Surcharge
G740	Service Charge
H151	Special Services
H300	Stamping
H370	Stenciling Charge
H430	Storage
H440	Straightening Charge
R060	Packing, Crating, and Handling Charge

SAC05	610	Amount	O	N2	1/15	Used
-------	-----	--------	---	----	------	------

Description: Monetary amount

General Mills Note:

The amount expressed has an implied 2-digit decimal. Example: \$5.63 would be sent as 563 and \$5.00 would be sent as 500.

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. L130204 - If SAC13 is present, then at least one of SAC02 or SAC04 is required.

7. C1413 - If SAC14 is present, then SAC13 is required.
8. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction to further the code in SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

General Mills Note:

These charges are called "condition records". It is the way General Mills is letting the vendor know of negotiated surcharges associated with the purchase order or a particular line.

DTM Date/Time Reference

Pos: 210	Max: 10
Detail - Optional	
Loop: PO1	Elements: 3

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 2)

Code Name

002 Delivery Requested
010 Requested Ship

DTM02	373	Date	X	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

DTM03	337	Time	X	TM	4/8	Used
-------	-----	------	---	----	-----	------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

General Mills Note:

General Mills sends HHMM

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

General Mills Note:

General Mills will send both DTM segments.

The Requested Ship date must be used by suppliers doing collect orders -- this is the date General Mills transportation will schedule shipment pickup.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 250	Max: 12
Detail - Optional	
Loop: PO1	Elements: 1

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD504	91	Transportation Method/Type Code	X	ID	1/2	Must use

Description: Code specifying the method or type of transportation for the shipment

CodeList Summary (Total Codes: 71, Included: 2)

Code Name

H	Customer Pickup
M	Motor (Common Carrier)

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

Loop Marking, Packaging, Loading

Pos: 305	Repeat: 200
Optional	
Loop: PKG	Elements: N/A

User Option (Usage): Used
Purpose: To describe marking, packaging, loading, and unloading requirements

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
305	PKG	Marking, Packaging, Loading	O	1		Must use

PKG Marking, Packaging, Loading

Pos: 305	Max: 1
Detail - Optional	
Loop: PKG	Elements: 3

User Option (Usage): Must use

Purpose: To describe marking, packaging, loading, and unloading requirements

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PKG01	349	Item Description Type	X	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PKG02	753	Packaging Characteristic Code	O	ID	1/5	Must use
-------	-----	-------------------------------	---	----	-----	----------

Description: Code specifying the marking, packaging, loading and related characteristics being described

CodeList Summary (Total Codes: 44, Included: 1)

Code Name

68 Skid/Pallet Type

PKG05	352	Description	X	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

General Mills Note:

General Mills will provide the pallet type in this element (CHEP, IGPS, SLIP SHEET, WHITE WOOD, PP= Packaging Pallet, etc.).

Syntax Rules:

1. R040506 - At least one of PKG04, PKG05 or PKG06 is required.
2. C0403 - If PKG04 is present, then PKG03 is required.
3. C0501 - If PKG05 is present, then PKG01 is required.

Semantics:

1. PKG04 should be used for industry-specific packaging description codes.

Comments:

1. Use the MEA (Measurements) Segment to define dimensions, tolerances, weights, counts, physical restrictions, etc.
2. If PKG01 equals "F", then PKG05 is used. If PKG01 equals "S", then PKG04 is used. If PKG01 equals "X", then both PKG04 and PKG05 are used.
3. Use PKG03 to indicate the organization that publishes the code list being referred to.
4. Special marking or tagging data can be given in PKG05 (description).

Loop Reference Identification

Pos: 330	Repeat: 1000
Optional	
Loop: N9	Elements: N/A

User Option (Usage): Used
Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
330	N9	Reference Identification	O	1		Must use
340	MSG	Message Text	O	1000		Must use

N9 Reference Identification

Pos: 330	Max: 1
Detail - Optional	
Loop: N9	Elements: 2

User Option (Usage): Must use
Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>				
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use				
Description: Code qualifying the Reference Identification										
CodeList Summary (Total Codes: 1503, Included: 1)										
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>55</td><td>Sequence Number</td></tr></table>							<u>Code</u>	<u>Name</u>	55	Sequence Number
<u>Code</u>	<u>Name</u>									
55	Sequence Number									
N903	369	Free-form Description	X	AN	1/45	Must use				
Description: Free-form descriptive text										

Syntax Rules:

- 1. R0203 - At least one of N902 or N903 is required.
- 2. C0605 - If N906 is present, then N905 is required.

Semantics:

- 1. N906 reflects the time zone which the time reflects.
- 2. N907 contains data relating to the value cited in N902.

General Mills Note:

PO Detail Messages

MSG Message Text

Pos: 340	Max: 1000
Detail - Optional	
Loop: N9	Elements: 1

User Option (Usage): Must use

Purpose: To provide a free-form format that allows the transmission of text information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MSG01	933	Free-Form Message Text	M	AN	1/264	Must use

Description: Free-form message text

Syntax Rules:

1. C0302 - If MSG03 is present, then MSG02 is required.

Semantics:

1. MSG03 is the number of lines to advance before printing.

Comments:

1. MSG02 is not related to the specific characteristics of a printer, but identifies top of page, advance a line, etc.
2. If MSG02 is "AA - Advance the specified number of lines before print" then MSG03 is required.

General Mills Note:

General Mills maximum length = 72

Loop Name

Pos: 350	Repeat: 200
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used
Purpose: To identify a party by type of organization, name, and code

Loop Summary:

Pos	Id	Segment Name	Req	Max Use	Repeat	Usage
350	N1	Name	O	1		Must use
360	N2	Additional Name Information	O	2		Used
370	N3	Address Information	O	2		Used
380	N4	Geographic Location	O	1		Must use

N1 Name

Pos: 350	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>								
N101	98	Entity Identifier Code	M	ID	2/3	Must use								
Description: Code identifying an organizational entity, a physical location, property or an individual														
CodeList Summary (Total Codes: 1312, Included: 3)														
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>MF</td><td>Manufacturer of Goods</td></tr><tr><td>SF</td><td>Ship From</td></tr><tr><td>ST</td><td>Ship To</td></tr></table>							<u>Code</u>	<u>Name</u>	MF	Manufacturer of Goods	SF	Ship From	ST	Ship To
<u>Code</u>	<u>Name</u>													
MF	Manufacturer of Goods													
SF	Ship From													
ST	Ship To													
N102	93	Name	X	AN	1/60	Must use								
Description: Free-form name														
N103	66	Identification Code Qualifier	X	ID	1/2	Must use								
Description: Code designating the system/method of code structure used for Identification Code (67)														
CodeList Summary (Total Codes: 215, Included: 1)														
<table><tr><th><u>Code</u></th><th><u>Name</u></th></tr><tr><td>92</td><td>Assigned by Buyer or Buyer's Agent</td></tr></table>							<u>Code</u>	<u>Name</u>	92	Assigned by Buyer or Buyer's Agent				
<u>Code</u>	<u>Name</u>													
92	Assigned by Buyer or Buyer's Agent													
N104	67	Identification Code	X	AN	2/80	Must use								
Description: Code identifying a party or other code														

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

General Mills Note:

If N101 = SF, General Mills will send the General Mills 10-digit number assigned for the partner's ShipFrom location.
If N101 = ST, General Mills will send General Mills ShipTo location number.

N2 Additional Name Information

Pos: 360	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used
Purpose: To specify additional names or those longer than 35 characters in length

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N201	93	Name	M	AN	1/60	Must use
		Description: Free-form name				
N202	93	Name	O	AN	1/60	Must use
		Description: Free-form name				

N3 Address Information

Pos: 370	Max: 2
Detail - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used
Purpose: To specify the location of the named party

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 380	Max: 1
Detail - Optional	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Must use
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Transaction Totals

Pos: 010	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

User Option (Usage): Must use
Purpose: To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		Must use

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: CTT	Elements: 1

User Option (Usage): Must use
Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

- 1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
- 2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

- 1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 030	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
SE01	96	Number of Included Segments	M	N0	1/10	Must use
Description: Total number of segments included in a transaction set including ST and SE segments						
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set						

Comments:

- 1. SE is the last segment of each transaction set.

GE Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of a functional group and to provide control information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included	M	N0	1/6	Must use
Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element						
GE02	28	Group Control Number	M	N0	1/9	Must use
Description: Assigned number originated and maintained by the sender						

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use
Purpose: To define the end of an interchange of zero or more functional groups and interchange-related control segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups	M	N0	1/5	Must use
Description: A count of the number of functional groups included in an interchange						
IEA02	I12	Interchange Control Number	M	N0	9/9	Must use
Description: A control number assigned by the interchange sender						